



NEW!



LIQUID GRAB SAMPLER

The Liquid Grab Sampler (**LGS**) adds value to the Lighthouse REMOTE Liquid Particle Counter by providing a reliable pump system and NEMA enclosure to help integrate it with process equipment and large facility monitoring systems.

The **LGS** was designed to provide reliable sampling in a variety of applications such as parts washing, waste water monitoring and process monitoring for many different environments.

It incorporates a state-of-the-art pump, precision pump speed control, precision flow meter and externally controlled low voltage pump switching. The **LGS** is easy to configure, operate and monitor. The Liquid Particle Counter (sold separately) provides particle count data in real time. All data can be transferred to a single computer or a facility monitoring system.

Designed and built by **Lighthouse Worldwide Solutions**, a name you can trust.

www.golighthouse.com

Features:

- ★ External Pump Control
- ★ RS485 MODBUS Interface
- ★ Easy to Use Features
- ★ Interfaces Easily to Building Management Systems
- ★ Maintains High 100 ml/min Flow Rate (User controllable)
- ★ Same Robust Data Features of the Lighthouse REMOTE Liquid Particle Counter
- ★ Designed for Reliability
- ★ Data Easily Downloaded to Computer
- ★ Used in Conjunction with Lighthouse REMOTE LPCs

Benefits:

- ★ 2 Year Warranty
- ★ User Friendly Interface
- ★ International Support
- ★ Low Cost of Ownership
- ★ Long Pump Life
- ★ Repeatable Liquid Flow Rate
- ★ Easily Installed and Set Up
- ★ Reliable 24/7 Operation
- ★ May be Used in a Variety of Applications

Applications:

- ★ Quantifying Particle Concentration in State of the Art High Purity Water Systems
- ★ Filter Efficiency Particle Measurements
- ★ Trending Analysis at Lower Particle Concentrations
- ★ Manufacturing Process Control
- ★ Process Bath Monitoring
- ★ Parts Cleaning Testing
- ★ Water Quality Monitoring



Specifications - LIQUID GRAB SAMPLER

Size Range - Refer to the LWS REMOTE Liquid Particle Counter Datasheet:	0.1 - 5.0µm
Flow Rate:	100 ml/min
Wetted Materials, Pump:	SS / PEEK / PTFE
Wetted Materials, Tubing:	PTFE
Wetted Materials, Flowmeter:	BUNA, PTFE, glass, Aluminum
Pump Motor:	DC Brushless, Magnetic Drive
Pump Type:	Gear, PTFE, Repeatable Flow Rate
LPC Connector Type:	Internal, Standard RJ-45; External, Ruggedized Hermetically-sealed RJ-45
Communication Modes:	RS-232 via RJ-45 to PC, RS-485/MODBUS
Supporting Software:	LMS Express RT and RT+; LMS and LMS Net
Fluid Connections:	1/4" Flare, PTFE
External Pump Control:	Screw Terminal Mount for Wiring to External Equipment DC Relay, 5VDC
Enclosure:	NEMA
Fluid Circulation:	Internal Pump, Manual Flow Control
Power:	100-240 VAC, 50-60 Hz
Dimensions:	7.0" (d) x 16.8" (w) x 17.2" (h) [17.8 x 42.7 x 43.7 cm]
Weight:	10 lbs (4.5 kg) as shipped (without RLPC)

Environmental Conditions

Operating: 50°F to 104°F (10°C to 40°C) / 20% to 95% relative humidity, non-condensing

Storage: 14°F to 122°F (-10°C to 50°C) / Up to 98% relative humidity, non-condensing

Accessories

Included: Operating Manual on CD, Power Supply

Manufactured by:



3041 Orchard Parkway
San Jose, CA 95134 USA
Tel: 408 228-9200
Fax: 408 228-9225
www.golighthouse.com
info@golighthouse.com



Distributed by:

